

# "WE MAKE THE KITCHEN BETTER!"

Toll Free: 855-855-0399 Em ail: info@atosausa.com www.atosa.com | www.atosausa.com California, Colorado, Florida, Georgia, Illinois, New Jersey, Ohio, Texas, Washington

MBF8506GR

# **Bottom Mount** Reach-In Refrigerators

### Standard Features

- Bottom mount compressor units with environmentally friendly R290 refrigerant
- Stainless steel exterior & interior
- Electronic temperature controller
- Maintains temperatures between 33°F - 40°F
- LED interior light(s)
- Recessed door handle(s)
- Door lock(s) standard
- Magnetic door gasket(s) standard for positive door seal
- Pre-installed casters
- Three(3) pre-installed shelves per section
- Down duct refrigeration to ensure even distribution of air

# Optional Accessories

 Extra shelves – includes 4 shelf clips per shelf MBF8505GR shelf part #: W0402393

MBF8507GR shelf part #: W0402387

MBF8508GR shelf part #: W0402387 left/right shelf,

part #: W0402388 middle shelf

For the best results of food preservation we recommend setting your refrigerator between 33 °F to 38 °F

- 1. Don't forget to leave the unit some room to breathe!
- 2. Please clean the condenser frequently to give the unit more fresh air.

















MBF8506GR



# "WE MAKE THE KITCHEN BETTER!"

Toll Free: 855-855-0399 Em ail: info@atosausa.com www.atosa.com | www.atosausa.com California, Colorado, Florida, Georgia, Illinois, New Jersey, Ohio, Texas, Washington


# **SPECIFICATIONS**

Models	Door	Capacity (Cu.Ft.)	Shelves	Casters (inch)	Amps (A)	Voltage (V/Hz/Ph)	HP	Refrigerant	Exterior Dimensions (inch)	Net Weight (lbs)	Gross Weight (lbs)
MBF8506GR	2	28.5	6	4	3.2	115/60/1	1/5	R290	39 <sup>1/2</sup> ×31 <sup>7/10</sup> ×83 <sup>1/10</sup>	317	365
					3						

## PLAN VIEW

#### MBF8506GR







\*Interior Dimensions

SELF-CLOSING AND STAY OPEN DOOR FEATURE

Epoxy shelves Door lock Down duct Casters Temperature control



