

## "WE MAKE THE KITCHEN BETTER!"

Toll Free: 855-855-0399 Em ail: info@atosausa.com www.atosa.com | www.atosausa.com California, Colorado, Florida, Georgia, Illinois, New Jersey, Ohio, Texas, Washington

#### MODELS:

RDCS-60

# Floor Model Refrigerated Square Display Cases

## Standard Features

- Stainless steel exterior & interior
- Full electronic digital controller
- Two (2) stainless steel adjustable shelves standard
- LED interior lighting on each shelf and top of cabinet
- Double pane tempered glass with front defog feature
- Rear mount compressor with environmentally friendly R-290 refrigerant
- Maintains temperatures between 33 °F 38 °F
- 2" casters standard
- Magnetic door gasket(s) standard for a positive door seal
- Two (2) rear sliding doors
- NEMA 5-15P plug standard
- Optional extended parts and labor warranty up to 5 years

For the best results of food preservation we recommend setting your refrigerator between 33  $^{\rm o}F$  to 38  $^{\rm o}F$ 

- 1. Don't forget to leave the unit some room to breathe!
- 2. Please clean the condenser frequently to give the unit more fresh air.









RDCS-60











# "WE MAKE THE KITCHEN BETTER!"

Toll Free: 855-855-0399 Email: info@atosausa.com www.atosa.com | www.atosausa.com California, Colorado, Florida, Georgia, Illinois, New Jersey, Ohio, Texas, Washington

## **SPECIFICATIONS**

Models	Door	Capacity (Cu.Ft.)	Shelves	Casters (inch)	Amps (A)	Voltage (V/Hz/Ph)	HP	Refrigerant	Exterior Dimensions (inch)	Net Weight (lbs)	Gross Weight (lbs)
RDCS-60	2	20.2	2	2	11.5	120/60/1	1/2	R290	59×29 <sup>1/2</sup> ×47 <sup>4/5</sup>	540	670

## PLAN VIEW

### RDCS-60







